



Product Information Sheet

Re-Issue Date: 01/04/03

Page 1 of 1

CHLORTEX

DESCRIPTION

An organic-based chlorine bleach.

CUSTOMER BENEFITS

1. May be added dry to the wheel.
2. Bleaches out stains and mildew.
3. Contains water softeners to utilise detergent from the previous bath.
4. Ideal for automatic washers with flush-in compartments.
5. Rinses freely.

DIRECTIONS FOR USE

- For normal bleaching operations add dry to the wheel.
- For light soil, 30 grams per 45 kgs.
- For medium soil, 60 grams per 45 kgs.
- For reject loads or mildew removal - approximately 350 grams per 45 kgs.
- These loads should run for 15 to 20 minutes to completely exhaust the chlorine. Follow with 4 rinses.

TEMPERATURE

Ideal range is 60°C to 70°C.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413