



Product Information Sheet

Issue Date: 01/03/09
Page 1 of 1

ENHANCE Hilite Sealer

DESCRIPTION

Tasman's ENHANCE is a breathable surface sealer which provides protection for concrete, terracotta tile, slate, pavers, limestone, brick, marble, granite and terrazzo while enhancing the colour of the surface to be sealed. It has been UV stabilised to ensure the sealed surface has the best possible protection against the sun's harmful rays. Tasman's ENHANCE is suitable for both commercial and domestic areas and areas such as kitchens, family rooms, hearths, bathrooms, shower recesses, patios and pool surrounds. Treated surfaces become easier to clean, maintain, and keep looking good for longer.

Tasman ENHANCE will prevent staining and allow low cost maintenance with NO STRIPPING ever. To reseal or touch-up, simply cover worn areas as needed.

BENEFITS

- Enrichment of natural colour of surface to be sealed
- Suitable for indoor and outdoor use
- Good resistance to abrasion, water, detergents and oil based stains.
- No stripping required, just reseal area
- Excellent levelling characteristics enabling surfaces to be sealed ranging from extremely porous tiles to dense tiles.
- Rapid hardness development.
- Fast set and tack-free times.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Australia: Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove Braeside Victoria 3195 Ph: 61-2-9587 6777 Fax: 61-2-9587 5255

New South Wales: Unit 3, 20-22 Foundry Road Seven Hills NSW 2147 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way Wangara WA 6065 Ph: 61-8-9248 9711 Fax: 61-8-9249 9183

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413



Product Information Sheet

Issue Date: 01/03/09

Page 2 of 2

ENHANCE Hilite Sealer

DIRECTIONS FOR USE

WARNING: Ensure good ventilation to dispense solvent vapours.
Keep away from naked flames, etc.

1. First test a small inconspicuous area. If the finish meets your requirements, continue to seal the remaining area
2. Surface to be sealed must be clean and dry, free from oil, grease, paint or acid, efflorescence loose flakes and grout residue.
3. New surfaces laid on sand and cement needs 4-6 weeks to allow mortar and grout to cure prior to sealing. New surfaces laid on adhesive can usually be sealed after 1-2 weeks.
4. Surfaces previously sealed with other sealers must have all traces of the old sealer removed with suitable strippers.
5. Prior to sealing, the surface to be sealed should be cleaned with Tasman's TILE KLEEN. It should be continually washed until after repeated washings no slate dust appears in the wash up water. Allow 24 hours for the cleaned area to dry. prior to sealing give the floor a quick vacuum.
6. Do NOT apply when the temperature is less than 8 deg C.
7. Apply three to four even generous coats of ENHANCE SEALER using a lambswool applicator or sprayer. Allow approximately 2-4 hours between applications. Some surfaces are extremely porous and will require additional coats. DO NOT USE A PAINT ROLLER.

PACKAGING

* 1 Lt Metal tin * 4 Lt Metal Drum * 20 Lt Metal drum

HEALTH AND SAFETY INFORMATION

See separate Material Safety Data Sheet available upon request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Australia: Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove Braeside Victoria 3195 Ph: 61-2-9587 6777 Fax: 61-2-9587 5255

New South Wales: Unit 3, 20-22 Foundry Road Seven Hills NSW 2147 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way Wangara WA 6065 Ph: 61-8-9248 9711 Fax: 61-8-9249 9183

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413