

# **MATERIAL SAFETY DATA SHEET**

**SECTION 1 – IDENTIFICATION** 

# **Product Name**

GRILLMASTER K3

**Product Name** 

**GRILL CLEAN** 

Recommended Use

Supplier ACN : Street Address Telephone Number Facsimilie Email Website Heavy Duty Oven & Grill Cleaner

TASMAN CHEMICALS PTY LTD 005 072 659 1-7 Bell Grove, Braeside , Victoria 3195 AUSTRALIA (03) 9587 6777 (03) 9587 5255 taschem@taschem.com.au www.tasmanchemicals.com.au

**Emergency Telephone Number** 

\_\_\_\_\_

1 800 334 556

# SECTION 2 – HAZARDS INDENTIFICATION

# Hazardous according to criteria of Safe Work Australia.

Hazard Category : C (Corrosive)

# **Risk Phrases**

R22	Harmful if swallowed
R35	Causes severe burns
R41	Risk of serious damage to eyes

# Safety Phrases

S1/2	Keep locked up and out of reach of children
S24/25	Avoid contact with skin and eyes
S26	In case of contact with eyes, rinse immediately with plenty of water and contact a Doctor
	or the Poisons Information Centre.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S45	In case of accident or if you feel unwell, seek medical advice immediately ( show the label wherever possible )

**Grill Clean** is classified as **Dangerous Goods Class 8** according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS			
Ingredient	CAS Number	Proportion (%m/m)	
Water	7732-18-5	Μ	
Sodium Hydroxide Alkaline salts	1310-73-2 527-07-1	M L	
Dye	Proprietary	L	
VH>60% H>30-60% M=10-30%	L=<10%		

Issue No 3 GRILLMASTER Issue Date : 01/07/12 Page 1 of 4 Prepared By : *Keith Sadlier* 

# **SECTION 4 – FIRST AID MEASURES**

# First Aid

Swallowed:	Immediately rinse mouth with water. If swallowed <u>DO NOT</u> induce vomiting. Give a 1-3 glasses of water to drink. If vomiting occurs, place victim head lower then hips to prevent vomiting entering lungs. Seek immediate medical assistance or contact the Poisons Information Centre immediately.
Eye:	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical assistance or contact the Poisons Information Centre immediately.
Skin:	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair immediately with running water. If swelling, redness, blistering or irritation occurs seek medical advice. For skin burns, immediately flood with plenty of water and cover with a clean dry dressing. Seek immediate medical advice
Inhaled	Remove victim from further exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical attention if effects persist.

# Advice to Doctor

Treat symptomatically and as for strongly alkaline corrosive material

# **SECTION 5 – FIRE FIGHTING MEASURES**

# **Fire/Explosion Hazard**

Corrosive to aluminium, zinc and tin, liberating flammable hydrogen gas. Reacts violently with acids. Reacts with ammonium salts liberating ammonia gas. Absorbs carbon dioxide from air. Reacts exothermically on dilution with water. Keep containers cool by spraying with water to prevent pressure building up inside the drums, causing them to burst.

# Extinguishing Media

Fire fighters must wear full protective clothing including self contained breathing apparatus. Not combustible, however reaction with metals will produce flammable hydrogen gas, which will burn if ignited. Use water fog ( or if unavailable fine water spray ), foam, dry agent ( carbon dioxide, dry chemical powder )

# SECTION 6 – ACCIDENTAL RELEASE MEASURES

# <u>Spills</u>

Increase ventilation. Wear protective equipment to prevent skin and eye contamination and inhalation of vapours or mists. Contain using sand or soil – prevent run off into drains and waterways. Use absorbent ( soil, sand vermiculite or other inert material). Collect and seal in properly labelled drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services. Caution heat may be evolved on contact with water

# SECTION 7 – HANDLING AND STORAGE

Handling : Avoid skin and eye contact

Issue No 3 GRILLMASTER Issue Date : 01/07/12 Storage : Under normal weather conditions store in a well-ventilated area. Store in a dry cool environment. Keep containers closed at all times when not in use. Store away from acids and ammonium salts. Do not store in aluminium or galvanised containers or use die cast zinc. Check regularly for leaks. Remove drum bungs slowly to release any internal pressure.

#### SECTION 8 – EXPOSURE CONTROLS / PERSONALPROTECTION

**Occupational Exposure Limits**: Occupational Exposure Limits: Threshold Limit Values Threshold Limit Value (TLV) = 2 mg/m<sup>3</sup> (Sodium Hydroxide) (Peak Limitation)

Peak Limitation : For some rapidly acting substances and irritants, the averaging of airborne concentration over an eight hour period is inappropriate. These substances may induce acute effects after relatively brief exposure to high concentrations and so the exposure standard for these substances represents a maximum or peak concentration to which workers may be exposed.

<u>Engineering Control Measures</u> : Ensure ventilation is adequate to maintain air concentrations below recommended exposure standard. Keep containers closed when not in use

#### Personal Protective Equipment :

Eye:	Use chemical face shield to prevent eye and face contact
Hands:	Use nitrile rubber gloves when skin contact is possible
Other:	Use rubber boots and apron to prevent skin contact
Respirator:	If inhalation risk exists wear canister type respirator suitable for particulates and alkaline gases.

Always wash hands before eating, drinking, smoking or using the toilet. Wash contaminated clothing and other protective equipment before storage and reuse.

#### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odour: Melting Point:	Clear Yellow Liquid 0oC	pH (as is): Flash Point: Valatilaa	13 to 14 Not applicable
Boiling Point: Density:@ 25°C	> 100°C (approximately) 1.20 grams/mL (approximately)	Volatiles Flammable Limits:	Water only Not applicable
Solubility:	Miscible		

#### SECTION 10 – STABILITY AND REACTIVITY

Stability Store away from acids and ammonium salts

ReactivityCorrosive to aluminium, zinc and tin, liberating flammable hydrogen gas.<br/>Absorbs carbon dioxide from air. Reacts exothermically on dilution with water

## SECTION 11 – TOXOLOGICAL INFORMATION

### Health Effects

No adverse health effects expected if the material is handled in accordance with the Material Safety Data Sheet. Symptoms that may arise if the material is mishandled are :

# Acute Effects

Swallowing:	May cause nausea, vomiting, diarrhoea, abdominal pain, swelling of the larynx and perforation of the gastrointestinal tract Oral LD50 = 500 mg/kg (rabbit)
Eye:	A severe eye irritant. May cause severe eye damage. Corrosive to eyes. May cause corneal damage. Eye ( rabbit) severe irritation 1mg / 30sec rinse
Issue No 3 GRILLN	ASTER Page 3 of 4

Issue Date : 01/07/12

Skin:	Contact with skin will result in severe irritation. Repeated or prolonged skin contact may cause burns and permanent damage. Corrosive to skin Dermal LD50 = 500 mg/ 24H (rabbit)
Inhaled:	Vapour or mist may be irritant to mucous membranes and respiratory tract. Possible harmful corrosive effects including lesions of the nasal septum, pulmonary oedema, pneumonitis and amphysema

## Chronic Effects

Principal routes of exposure are by accidental skin or eye contact Prolonged or repeated skin contact may have a corrosive action on human tissues

# SECTION 12 – ECOLOGICAL INFORMATION

Avoid contaminating waterways. Spills should be contained, absorbed by sand or earth and placed in sealed plastic or epoxy-lined drums for disposal

# **SECTION 13 – DISPOSAL CONSIDERATIONS**

Refer to Waste Management Authority .

# **SECTION 14 – TRANSPORT INFORMATION**

Classified as a Dangerous Good by the Criteria of the Australian Dangerous Good Code

Proper Shipping Name :	Sodium Hydroxide solution 8	UN No :	1824
Dangerous Goods Class :		Subsidiary Risk :	Not applicable
Hazchem Code :	2R	Packing Group :	III

#### **SECTION 15 – REGULATORY INFORMATION**

Classification Based upon information, classified as hazardous according to criteria of Safe Work Australia

Poisons Schedule Schedule 6

#### **SECTION 16 – OTHER INFORMATION**

Contact Points Organisation	<b>Location</b>	<u>Telephone</u>	Ask For
Tasman Chemicals Pty Ltd	Braeside, Victoria, Australia	(03) 9587 6777	Technical Manager
Poisons Information Centre		13 1126	

MSDS are updated frequently. Please ensure that you have a current copy.

This MSDS summarises our best knowledge of the health and safety hazard information of the product; how to safely handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Tasman Chemicals Pty Ltd. Our responsibility for products sold are subject to our standard terms and conditions, a copy of which appears on all invoices. It is also available on request. Where health or safety data given discloses a risk to the user or environment, it is the responsibility of the Purchaser to pass on that information to employees or those who may be using the product, ensuring that adequate safety procedures are used including good industrial hygiene.