



Product Information Sheet

Re-Issue Date: 01/04/03

Page 1 of 2

HERITAGE FINISH NATURAL PENETRATING SEALER

DESCRIPTION

HERITAGE FINISH is a clear light buff coloured solution designed for application to a wide variety of porous surfaces in order to protect those surfaces from soiling and staining.

HERITAGE FINISH does not markedly change the appearance of the surface being treated.

APPLICATION

Suitable for commercial and domestic areas on the following surfaces:

- ⇒ Unglazed tiles & quarry tiles
- ⇒ Slate
- ⇒ Terracotta
- ⇒ Stone
- ⇒ Brick
- ⇒ Concrete

The product can also be used both internally and externally and is not subject to change in appearance and will not exhibit yellowing characteristics.

BENEFITS

- Retains the natural look of the material being treated without markedly changing the original appearance of the surface.
- Helps to prevent staining caused by most common soils and food residues.
- Is suitable for use on a wide variety of surfaces including tiles, slate, terracotta, stone, brick and concrete.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413



Product Information Sheet

HERITAGE FINISH

Page 2 of 2

DIRECTIONS FOR USE

Ensure that the surface to be sealed is completely clean and dry. Any stains and soiling present on the surface should be removed using a suitable detergent prior to sealing.

Apply the product neat using a paint brush and coat the entire area to be treated.

We recommend that two coats of the product be applied to most surfaces allowing 6 hours between applications. On very porous surfaces 3 coats may be necessary.

Allow 24 hours for product to cure before allowing full use of the treated area.

Re-application of HERITAGE FINISH may be necessary after a period of time dependent upon wear and tear.

COVERAGE

One litre will cover approximately 15-25m² dependent on porosity of the surface being treated.

- NOTE
1. As there are wide variations of surfaces and application procedures it is recommended that a small area be treated with HERITAGE FINISH prior to treating the entire area. Once satisfied that the product and application techniques are satisfactory, the entire area can be treated.
 2. HERITAGE FINISH should not be used to re-coat any surface that has been previously treated with other sealers.
 3. In order to gain maximum benefit from the use of HERITAGE FINISH it is recommended that all soiling materials be removed from treated floors as soon as possible after a spill.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413