



## Product Information Sheet

Re-Issue Date: 01/04/2017

Page 1 of 2

# PREMIUM SLATE SEAL

## DESCRIPTION

PREMIUM SLATE SEAL is a clear solvent based acrylic sealer which enhances the natural beauty inherent in new or old slate floors.

PREMIUM SLATE SEALER imparts a high gloss finish, is highly resistant to yellowing from ultra violet light and imparts a long lasting finish to sealed surfaces.

PREMIUM SLATE SEAL prevents staining and allows easy low cost maintenance.

## APPLICATION

PREMIUM SLATE SEAL is suitable for commercial and domestic slate areas, unglazed terracotta, paving bricks and most interior and exterior applications such as kitchens, family rooms, hearths, and patios.

## BENEFITS

- Excellent re-coatability
- High resistance to yellowing
- High resistance to wear in heavy traffic areas
- High gloss finish on slate and other hard surfaces
- High solids formulation for long life
- Prevents staining and allows easy low cost maintenance

## DIRECTIONS FOR USE

**WARNING:** Ensure good ventilation to dispense solvent vapours. Keep away from naked flames, etc.

1. Surfaces to be sealed must be thoroughly clean and dry and free from grease, oil, paint, acid, efflorescence and traces of grout.
2. Newly laid areas need 4 - 6 days to allow mortar and grout to cure and dry prior to sealing. slate which has been acid washed needs at least 4 weeks for slate to dry prior to sealing otherwise floor can turn white.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

**Australia: Tasman Chemicals Pty Ltd**

**Victoria:** 1-7 Bell Grove Braeside Victoria 3195 Ph: 61-2-9587 6777 Fax: 61-2-9587 5255

**New South Wales:** Unit 12, 155 Glendenning Road Glendenning 2761 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

**South Australia:** 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

**Tasmania:** 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

**Western Australia:** Unit 1, 23 Dillington Pass, Lansdale Pass WA 6065 Ph: 61-8-9309 2100 Fax: 61-8-9309 2511

**Queensland:** Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413



## Product Information Sheet

Re-Issue Date: 01/04/2017

Page 2 of 2

# PREMIUM SLATE SEAL

## **DIRECTIONS FOR USE** ( continued )

3. Surfaces previously sealed with slate sealers other than Tasman Slate Seal, or polished surfaces, must have all traces of old sealer and polish completely removed with suitable strippers
4. Prior to sealing the slate, the slate should be cleaned with Tasman's TILE KLEEN. It should be continually washed until, after repeated washings, no slate dust appears in the wash up water. Allow at least 24 hours for the cleaned area to dry. Prior to sealing give the floor a quick vacuum.
5. Do not seal hot surfaces - all surfaces must be cool.
6. Apply 3-4 even generous coats of PREMIUM SLATE SEAL with a paint brush. Allow approximately 4 hours or until touch dry between coats.
7. Avoid heavy traffic for 48 hours after sealing.
8. To maintain seal in dry areas apply Tasman Slate Finish as per instructions. Otherwise simply apply Tasman PREMIUM SLATE SEAL to worn/dull areas as required.

**COVERAGE:** 1 litre will cover approx. 8-10 square metres with two coats.

**CLEAN UP:** Brushes must be cleaned with Tasman Slate Seal Solvent or softened by soaking in Tasman PREMIUM SLATE SEAL 10 minutes prior to reapplication

## **HEALTH AND SAFETY INFORMATION**

See Safety Data Sheet ( SDS ) for reference available on request

**PACKAGING**          1 Litre , 4 Litre, 10 Litre, 20 Litre

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

**Australia: Tasman Chemicals Pty Ltd**

**Victoria:** 1-7 Bell Grove Braeside Victoria 3195 Ph: 61-2-9587 6777 Fax: 61-2-9587 5255

**New South Wales:** Unit 12, 155 Glendenning Road Glendenning 2761 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

**South Australia:** 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

**Tasmania:** 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

**Western Australia:** Unit 1, 23 Dillington Pass, Lansdale Pass WA 6065 Ph: 61-8-9309 2100 Fax: 61-8-9309 2511

**Queensland:** Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413